



SLOTTED Ball Bearing Disc Springs Dimensions:								Deflection at F= 0.75h	
Ball Bearing Reference Number			Outer Diameter OD	Inner Diameter ID	Thickness T	Height h	Overall Height	F Deflections in mm	P Load in N
	623		9.80	6.20	0.15	0.45	0.60	0.35	13
	624		12.80	7.20	0.20	0.45	0.65	0.35	18
	625	634	15.80	8.20	0.25	0.50	0.75	0.40	20
	626	635	18.80	9.20	0.25	0.75	1.00	0.55	20
607			18.80	10.20	0.25	0.80	1.05	0.60	24
608	627		21.80	12.30	0.25	1.00	1.25	0.75	24
609			23.70	14.30	0.30	1.00	1.30	0.75	25
6000	629		25.70	14.30	0.30	1.10	1.40	0.80	28
6001			27.70	17.30	0.35	1.10	1.45	0.80	31
	6200		29.70	17.30	0.35	1.20	1.55	0.90	32
6002	6201		31.70	20.40	0.35	1.20	1.55	0.90	33
		6300	34.60	20.40	0.40	1.25	1.65	1.00	32
6003	6202		34.60	22.40	0.35	1.20	1.55	0.90	32
		6301	36.60	20.40	0.40	1.50	1.90	1.10	35
	6203		39.60	25.50	0.40	1.50	1.90	1.10	37
6004		6302	41.60	25.50	0.45	1.60	2.05	1.20	39
6005	6204	6303	46.50	30.50	0.45	1.60	2.05	1.20	44
	6205	6304	51.50	35.50	0.45	1.65	2.10	1.25	47
6006			54.50	40.50	0.45	1.70	2.15	1.30	53
6007	6206	6305	61.50	40.50	0.55	2.00	2.55	1.50	54
6008			67.50	50.50	0.50	2.10	2.60	1.60	78
		6306	71.50	45.50	0.60	2.30	2.90	1.70	74
	6207		71.50	50.50	0.60	2.30	2.90	1.70	127
6009			74.50	55.50	0.60	2.30	2.90	1.70	91
		6307	79.50	50.50	0.70	2.40	3.10	1.80	83
6010	6208		79.50	55.50	0.70	2.20	2.90	1.65	127
	6209		84.50	60.50	0.75	2.40	3.15	1.80	78
		6308	89.50	60.50	0.80	2.50	3.30	1.90	104
6011	6210		89.50	65.50	0.80	2.60	3.40	1.95	189
6012			94.50	75.50	0.80	2.65	3.45	2.00	206

Registered Office : C 436, Siddhivinayak Tower, Makarba, Ahmedabad 380051, India

Factory: Plot No. 139/2, GIDC Limbdi, 363421, Gujarat, India

Email: info@harshvijayexim.com | **website:** www.harshvijayexim.com | **Tel:** +91 79 45041175